



## SPECIFICATION

1. Connector A: SC/PC MM P/N: 11-HM-1-3
2. Connector B: SC/PC MM P/N: 11-HM-1-3
3. Cable Type: Duplex  $\phi 3.0\text{mm}$  62.5/125 $\mu\text{m}$  MM
4. Length: 10M
5. Jacket Color: Orange
6. Insertion Loss: <0.5 dB
7. Package: Individual Bag

## OPERATION

Fiber Extension:  $-0.05\mu\text{m} < H < +0.05\mu\text{m}$   
 Ferrule End-face Radius:  $10 < R < 25\text{mm}$   
 Apex Offset: < 50 $\mu\text{m}$   
 Increase in insertion loss after 500 mating: 0.2 dB Max.  
 Operation Temperature:  $-20^{\circ}$  to  $+70^{\circ}$   
 Storage Temperature:  $-40^{\circ}$  to  $+80^{\circ}$   
 Humidity (non-condensing) 95%RH

	DSGN	MAER	18.MAY.2004	ITEM NO:	AL-6SCSC-10I
	UNIT	M/M			
SCALE	1/2	CHK		APPR	Duplex $\phi 3.0\text{mm}$ 62.5/125 $\mu\text{m}$ MM
DWG NO:	AL-6SCSC-10I	<b>ASSMANN Electronic Components</b>			