



## SPECIFICATION

1. Connector A: LC/PC MM P/N: 11-PM-1-1
2. Connector B: SC/PC MM P/N: 11-HM-1-3
3. Cable Type: Duplex  $\varnothing 3.0\text{mm}$  50/125um MM
4. Length: 3M
5. Jacket Color: Orange
6. Insertion Loss: <0.5 dB
7. Package: Individual Bag

## OPERATION

Fiber Extention:  $-0.05\mu\text{m} < H < +0.05\mu\text{m}$   
 Ferrule End-face Radius:  $10 < R < 25\text{mm}$   
 Apex Offset:  $< 50\mu\text{m}$   
 Increase in insertion loss after 500 mating: 0.2 dB Max.  
 Operation Temperature:  $-20^\circ$  to  $+70^\circ$   
 Storage Temperature:  $-40^\circ$  to  $+80^\circ$   
 Humidity (non-condensing) 95%RH

	DSGN	MAER	18.MAY.2004	ITEM NO:	AL-5LCSC-03I
	CHK				
UNIT	M / M	APPR			Duplex $\varnothing 3.0\text{mm}$ 50/125um MM
SCALE		<b>ASSMANN Electronic Components</b>			
DWG NO:	AL-5LCSC-03I				