



SPECIFICATION

1. Connector A: MT-RJ MM P/N: 11-MM-1-1
2. Connector B: LC/PC MM P/N: 11-PM-1-1
3. Cable Type: Duplex ϕ 3.0mm 62.5/125um MM
4. Length: xM
5. Jacket Color: Orange
6. Insertion Loss: <0.5 dB
7. Package: Individual Bag

OPERATION

Fiber Extention: $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
 Ferrule End-face Radius: $10 < R < 25\text{mm}$
 Apex Offset: < 50um
 Increase in insertion loss after 500 mating: 0.2 dB Max.
 Operation Temperature: -20° to $+70^{\circ}$
 Storage Temperature: -40° to $+80^{\circ}$
 Humidity (non-condensing) 95%RH

| | | | | | |
|---------------------------|--------------------------------------|------|-------------|----------|-----------------------------------|
| | DSGN | MAER | 18.MAY.2004 | ITEM NO: | AL-6MTRJLC-02I |
| | UNIT | M/M | | | |
| SCALE | | APPR | | | Duplex ϕ 3.0mm 62.5/125um MM |
| DWG NO: AL-6MTRJLC-02I | ASSMANN Electronic Components | | | | |